


INTELLIGENT SERIES

4" Industrial Barcode Printer



GI-2408T



KEY FEATURES

- Rugged and reliable construction, industry-standard performance for high volume label printing
- Easy to load print media and ribbon, easy to operate
- Equipped with high-quality touch screen, bringing users a smart, intuitive and convenient operation experience

INTELLIGENT SERIES 4" Industrial Thermal Transfer Barcode Printer

MODEL	GI-2408T	GI-3406T	GI-2408T	GI-3406T
Level	Standard	Standard	Empower	Empower
Resolution	8dots/mm (203DPI)	12dots/mm (300DPI)	8dots/mm (203DPI)	12dots/mm (300DPI)
Printing Method	Thermal Transfer & Direct Thermal			
Max. print speed	203mm(8")/second	152mm(6")/second	203mm(8")/second	152mm(6")/second
Max. print width	104 mm (4.09")	108.4 mm (4.27")	104 mm (4.09")	108.4 mm (4.27")
Memory RAM	128 MB SDRAM			
Memory ROM	128 MB Flash Memory			
Interface	<ul style="list-style-type: none"> • USB 2.0 High Speed 480Mbps • USB Host 2.0, for scanner or PC keyboard • RS-232 		<ul style="list-style-type: none"> • Internal Ethernet 10/100Mbps • Internal Bluetooth 4.0 (factory option) • Internal WiFi (factory option) 	
User Interface	<ul style="list-style-type: none"> • 1 power switch • 2 buttons (Feed & Pause) • 4 LEDs (Online, Error, Ribbon, Communication status) 		<ul style="list-style-type: none"> • 1 power switch • 1 buttons (Feed) • 1 LEDs(Online, Error, Ribbon status) • Capacitive Touch Screen, TFT LCD 4.3" 16 bits Color, 272 x 480 pixels, with back lights 	
Power	Input: AC 90-240V, 1.5A, 50-60Hz, Output: DC 24V, 5A, 120W			
Internal fonts	<ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • True type font engine (need download scalable font file) 			
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Plessey, PostCode, Telepen			
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix			
Rotation	Font and barcode support 0, 90, 180, 270 degree			
Printer language	Compatible to TSPL, EPL, EPL 2, ZPL, ZPL II, DPL			
Physical dimension	425mm (L) * 255mm (W) * 265mm (H)			
Net Weight	9.65kg			



Applications

- Logistics
- Shipping
- Retail
- Warehousing
- Manufacturing
- Transportation

Environmental concern

Comply with RoHS, REACH, WEEE

Environment condition

Operation: 5 ~ 40°C, 25 ~ 85% non-condensing
Storage: -40 ~ 60°C, 10 ~ 90% non-condensing

Safety regulation

FCC Class A, CE Class A, CCC, BIS, CB

Accessories

- Windows labeling software CD disk
- Quick start guide
- USB cable
- Power cord
- 1" ribbon spindle x 2 for 450M ribbon

